

PowerMust MSB16 RM**Features**

- Provides continuous power to connected equipment during UPS maintenance with rack mount compatible
- Easy operation with simple rotary switch and indicators
- Adjustable master-slave function for energy saving
- Provides a large number of sockets for extended usage
- Provides rack and tower designs to fit into a diverse working environment
- Simple plug-and-play connectivity for both input and output
- Suitable for all UPSs up to 3KVA

Specification

Product type	Maintenance bypass switch of uninterrupted power supply	
Current Rating	16 A max. for 208/220/230/240 VAC 20 A max. for 110/115/120/127 VAC	
Master/Slave Function	Yes. When power consumption in Master outlet is lower than 20W ($\pm 5\%$), it will shut off the power for slave outlets.	
Connection		
Input	AC Power	1 x IEC (16 A) connector and 1 x customized plug cable
	UPS Input	1 x IEC (16 A) connector and 1 x cable (16A - 10A IEC cable for 1K/2K, 16A - 16A IEC cable for 3K)
	UPS Output	1 x IEC (16 A) connector and 1 x cable (16A - 10A IEC cable for 1K/2K, 16A - 16A IEC cable for 3K)
Output	5 x IEC 10A sockets + 1 x IEC 16A socket (with 2 circuit breakers)	
Physical		
Dimension, DXWXH (mm)	80 x 438 x 50	
Net weight (kg)	1,5	
Environment		
Operating Temperature	20-90 % RH @ 0-40°C (non-condensing)	
Accessories	N/A	