

## PowerMust 600 Plus Line Int., Schuko



PM 600 Plus Top side



PM 600 Plus side

### Features

- Built in super smart charger, 90% fully charged in 4 hours
- Boost and Buck AVR for voltage stabilization
- Built-in USB communication port
- RJ-45 protection
- Easy replacement battery compartment
- Discharge, overcharge and overload protection
- Visual and audible Alarm system
- Simulated sinewave output

## PowerMust 600 Plus Line Int., Schuko

### Specification

<b>MODEL</b>	<b>PowerMust 600 Plus Line Int.</b>
<b>INPUT</b>	
Capacity	625VA/375W
Nominal Voltage	220/230/240 VAC
Voltage Range	170-285 VAC
Frequency Range	50/60 Hz (auto sensing)
<b>OUTPUT</b>	
AC Voltage Regulation (Batt. Mode)	± 10%
Frequency Range (Batt. Mode)	50 / 60 Hz ± 1 Hz
Transfer Time	Typical 2-6 ms, 10 ms max.
Line Mode Voltage	Same as input voltage
Waveform (Batt. Mode)	Simulated Sinewave
Protection	Discharge, Overcharging and Overload protection
<b>BATTERY</b>	
Battery Type	12 V/ 7 AH x1
Recharge Time	4 hours (recharge to 90% capacity)
<b>INDICATORS</b>	
Line Mode Normal	Green lighting
Battery Normal	Yellow flashing
Battery Low	
Fault	Red lighting
<b>AUDIBLE ALARM</b>	
Battery Mode	Sounding every 10 seconds
Low Battery at battery mode	Sounding every second
Fault	Continuously sounding
<b>PHYSICAL</b>	
Dimension, D x W x H (mm)	292 x 199 x 91
Net Weight (kgs)	5,3
<b>ENVIRONMENT</b>	
Operation Humidity	0-90% RH @ 0-40° C (non-condensing)
<b>INTERFACE</b>	
Power Cord Connector	AC power cable
Outlet	Schuko x 5
Phoneline/ Network protection R45	Yes
USB Port	Yes
LED/LCD	LED x 3